



# 脱皮鉗 WIRE STRIPPER




## ・脱皮鉗



NO.3000



NO.3500E



NO.3600

品 號	型 號	全 長	重 量	線芯直徑および公稱斷面積	柄 色
103900100	3000A	170	350	0.5/1.2/1.6/2.0mm(單線用)	綠
103900200	3000B	170	350	1.0/1.6/2.0/2.6/3.2mm(單線用)	赤
103900300	3000C	170	350	0.9/1.25/2.0/3.5/5.5mm <sup>2</sup> (より線用)	黑
103900400	3000D	170	350	1.5W/1.8W(平行ビニール線用)	オレンジ
103900500	3000E	170	350	3.8/0.5mm(同軸ケーブル用)	紺
103900600	3000F	170	350	1.8/1.65×2(テレビフィーダー線用)	青
103900800	3500E-1	155	100	AWG 24/22/20/16/14/12	赤
103900810	3500E-2	155	100	AWG 30/28/26/24/22/20/18	黄
103900850	3500E-6	155	100	AWG 26/24/22/20/18/16	赤
103900860	3500E-7	155	100	AWG 30/28/26/24/22	黄
103900900	3600M	140	165	AWG 24/22/20	赤
103900910	3600N	140	165	AWG 28/26/24	オレンジ

## ■ワイヤーストリッパー適應電線サイズ一覽表(AWG・MM・MM<sup>2</sup>)

電 線 サイズ	AWG	30	28	26	24	22	21	20	18	17	16	14	12	10	8	7	3
	MM	0.25	0.32	0.40	0.51	0.64	0.72	0.81	1.02	1.15	1.29	1.63	2.05	2.59	3.26	3.67	5.83
	MM <sup>2</sup>	0.25	0.08	0.13	0.20	0.32	0.41	0.52	0.82	1.04	1.31	2.08	3.31	5.26	8.37	10.55	26.7
3000A	單線(mm)				0.5						1.2	1.6	2.0				
3000B	單線(mm)							1.0				1.6	2.0	2.6	3.2		
3000C	より線(mm <sup>2</sup> )								0.9	1.25	2.0	3.5	5.5				
3000D	平行ビニール線(mm)							0.75×2		1.25×2							
3000E	同軸ケーブル線(mm)				0.5											3.8	
3000G	同軸ケーブル線(mm)						0.8									3.8	5.6
3000VA	VA・IV線(mm)										1.6×2	2.0×2					
3600M	單線(mm)				0.5	0.65		0.8									
	より線(mm <sup>2</sup> )				0.2	0.3		0.5									
3600N	單線(mm)		0.3	0.4	0.5												
	より線(mm <sup>2</sup> )		0.08	0.13	0.2												
3500E-1	單線(mm)				0.5	0.65		0.8	1.0		1.3	1.6	2.0				
	より線(mm <sup>2</sup> )				0.2	0.3		0.5	0.8		1.3	2.0	3.3				
3500E-2	單線(mm)	0.25	0.3	0.4	0.5	0.65		0.8	1.0								
	より線(mm <sup>2</sup> )	0.58	0.08	0.13	0.2	0.3		0.5	0.8								
EW-200S CW-200S	より線(mm <sup>2</sup> )					0.3	0.4	0.5	0.75		1.25	2.0					