



快速接頭

HI CUPLA



P PLUG

PH



H(Hose Nipple)

PM



M(Male Screw)

PF



F(Female Screw)

—>—<— (片路開閉式) 鋼鐵製 SS41
黑銅製 BSBM
不鏽鋼製 SuS

P SOCKET

SH



H(Hose Nipple)

SF



F(Female Screw)

SM



M(Male Screw)

註：X-100價格另議

PLUG 種類		SS41	BSBM	SUS
品 號	型 式	價格請洽業務單位		
112000100	20 PH			
112000110	30 PH			
112000120	40 PH			
112000200	20 PM			
112000210	30 PM			
112000220	40 PM			
112000300	20 PF			
112000310	30 PF			
112000320	40 PF			

SOCKET 種類		SS41 (SG)	BSBM (SG)	SUS (SG)
品 號	型 式	價格請洽業務單位		
112000500	20 SH			
112000510	30 SH			
112000520	40 SH			
112000600	20 SM			
112000610	30 SM			
112000620	40 SM			
112000700	20 SF			
112000710	30 SF			
112000720	40 SF			

112000130	400 PH 1/2"			
112000230	400 PM 1/2"			
112000330	400 PF 1/2"			
112000140	600 PH 3/4"			
112000240	600 PM 3/4"			
112000340	600 PF 3/4"			
112000150	800 PH 1"			
112000250	800 PM 1"			
112000350	800 PF 1"			

112000530	400 SH 1/2"			
112000630	400 SM 1/2"			
112000730	400 SF 1/2"			
112000540	600 SH 3/4"			
112000640	600 SM 3/4"			
112000740	600 SF 3/4"			
112000550	800 SH 1"			
112000650	800 SM 1"			
112000750	800 SF 1"			

耐 壓 力：最高壓力20kg/cm²，破壞壓力60kg/cm²。

使用溫度範圍：-20℃ ~ +80℃。

主要適用流體：空氣、水。

用 途：各種空氣配管、空氣工具、空氣壓機器、水道配管。