




# 快速接頭


## MICRO CUPLA




SH




SM



SM




SHL




電腦編號	規格型式	Ls	φD	A	φT	φBs	Hs	C	E
112090500	MC-04SH	27.5	9.5	8	4.8	2.5	—	—	—
112090650	MC-05SM	24	9.5	4.5	M5×0.8	2.5	六角9	—	—
112090750	MC-10SM	30	9.5	9	PT1/8	2.5	六角11	—	—
112090550	MC-04SHL	29.5	9.5	8	4.8	2.5	六角9	24.5	18
112090510	MC-04SHB	35	9.5	8	4.8	2.5	六角11	15	—


PH




PM






PM



PHL



電腦編號	規格型式	Ls	C	A	φHP	φT	φBp	E
112090100	MC-04PH	19	9.2	8	5.5	4.8	2.5	—
112090600	MC-05PM	17	9.2	4.5	六角7	M5×0.8	2.5	—
112090700	MC-10PM	26	12.5	9	六角11	PT1/8	2.5	—
112090150	MC-04PHL	22.5	17.5	8	六角7	4.8	2.5	18



電腦編號	規格型式	L	L <sub>1</sub>	L <sub>2</sub>	A	B	C	E	F	T	H
112090000	MC-03	78	31	16	27.5	23	16	15	48	2-PT1/8	4角16
112090900	MC-05	110	31	48	27.5	23	16	15	80	2-PT1/8	4角16
112091000	MC-10	190	31	128	27.5	23	16	15	160	2-PT1/8	4角16

耐 壓 力：最高壓力15kg/cm<sup>2</sup>  
 使用溫度範圍：- 20℃~+ 80℃  
 用 途：氣壓缸、電磁弁等各種配管  
 材 質：銅